


# MODEL RANGE



Volvo Trucks. Driving Progress

FH 16 6x4 Platform - Rear Air Suspension FH 64 R6HA



## Chassis Dimensions [mm]

WB Wheelbase	3700	3900	4300	4600	4900	5200	5600
A Overall Chassis Length	8460	8760	9410	9860	10310	10810	11410
D Center of rear axle to front of body	2690	2890	3290	3590	3890	4190	4590
N Rear Overhang (Min.)	825	825	825	825	825	825	825
N Rear Overhang (Max.)	2025	2125	2375	2525	2675	2875	3075
T Theoretical Wheelbase	4385	4585	4985	5285	5585	5885	6285
Y Center of Gravity for Payload (Min.)	-186	-165	-123	-92	-63	-31	7
Y Center of Gravity for Payload (Max.)	66	99	166	215	262	312	375

## Chassis Weights [kg]

Front Axle	5030	5040	5055	5070	5090	5100	5120
Rear Bogie	3600	3615	3660	3685	3720	3750	3785
Kerb Weight	8630	8655	8715	8755	8810	8850	8905
Payload (including body, driver, fuel, etc.)	17370	17345	17285	17245	17190	17150	17095

## Turning Diameter [mm]

Turning Circle Diameter Kerb to Kerb	15500	16100	17300	18200	19100	20000	21300
Turning Circle Diameter Wall to Wall	16800	17400	18700	19600	20500	21400	22600

## Plated Weights [kg]

	Plated	Design
Gross Vehicle Weight	26000	29000
Gross Combination Weight	44000	44000
Front Axle	8000	8000
Rear Bogie	19000	21000

## Important Notes

### Chassis Dimensions

Cab Height: +305 mm for CAB-HSLP, -283 mm for CAB-LSLP, +450 mm for CAB-XHSL.

D-measure includes a front clearance of 50 mm and for rigid trucks also a subframe of 100 mm.

Height can vary  $\pm 20$  mm for leaf and  $\pm 10$  mm for air suspension.

All dimensions are for unladen chassis and any tag axles down. Chassis height used: CHH-HIGH.

Rear overhang used for vehicle weight calculation is the maximum rear overhang (N Max.) for selected wheelbase.

Height change when chassis height CHH-MED,FRAME266: 0 mm.

Weight and dimensions are based upon the following tyres:

Front Axle Tyres: 315/80R22.5  
Drive Axle Tyres: 315/80R22.5

**Chassis weight includes oil, water, AdBlue, 0 litres fuel and without driver. Kerb weight can vary  $\pm 3\%$ .**

Turning diameters are theoretically calculated.

Legal weights can differ from country to country.

For more detailed weight information, including optional equipment weights, ask your Volvo sales contact to enter your specification into the Volvo Weight Information system (WIS).

Do NOT use this drawing for bodybuilding. Refer to Volvo Bodybuilder Instructions and chassis assembly drawing FH64R6HA.

# MODEL RANGE

## FH 16 6x4 Platform - Rear Air Suspension FH 64 R6HA

### TRUCK USE

- **RC-ROUGH** Operating class on/off road
- **RC-SMOOTH** Operating class highway
- **SWAPBODY** Swap body vehicle preparation
- **TIPP-PRE** Tipper vehicle preparation
- **UNIFORM** Basic platform vehicle

### CORE COMPONENTS

- **CHH-HIGH** Chassis height high - N3 "On Road" chassis - For a specific loading height always check the unique BEP chassis drawing
- **CHH-MED** Chassis height medium - For a specific loading height always check the unique BEP chassis drawing
- **FH16HSLP** Globetrotter cab - all steel safety cage design with roof mounted emergency escape hatch. Designed and built to Swedish impact and ECE R29 regulations
- **FH16SLP** Sleeper cab - all steel safety cage design with roof mounted emergency escape hatch. Designed and built to Swedish impact and ECE R29 regulations
- **FH16XHSL** Globetrotter XL cab - all steel safety cage design with roof mounted emergency escape hatch. Designed and built to Swedish impact and ECE R29 regulations
- **D16K550** D16K550 16litre engine developing 550hp at 1550-1900rpm SCR & EGR. Peak torque 2900Nm at 900-1350rpm. 2800Nm at 900-1400rpm with manual gearbox
- **D16K650** D16K650 16litre engine developing 650hp at 1450-1900rpm SCR & EGR. Peak torque 3150Nm at 950-1450rpm.
- **D16K750** D16K750 16litre engine developing 750hp at 1600-1800rpm SCR & EGR. Peak torque 3550Nm at 950-1400rpm.
- **EBR-EPG** Exhaust brake controlled by steering column switch
- **EBR-VEB+** Volvo engine brake + and exhaust pressure governor, enhanced performance from additional exhaust rocker control. Retardation 375kW
- **AT2812F** AT2812E 12-speed "I-shift" automated mechanical gearbox suitable for gross train weights up to 60 tonne refer to sales engineering when used in conjunction with a PTO
- **ATO3112F** ATO3112F 12-speed "I-shift" overdrive automated mechanical gearbox suitable for gross train weights up to 60tonne refer to sales engineering when used in conjunction with a PTO
- **ATO3512F** ATO3512F 12-speed "I-shift" automated mechanical gearbox suitable for gross train weights up to 60 tonne refer to sales engineering when used in conjunction with a PTO
- **TAAXLIFT** Rear axle lift for double drive bogie CONTACT VOLVO SALES ENGINEERING to check lift capability
- **RTH2610F** RTH2610F hub reduction tandem 26tonne drive axles, GCW 100 tonnes with differential and cross locks\* \* Cross locks replaced by a dog clutch if tandem axle lift is specified
- **RTS2310A** RTS2310A single reduction tandem 23tonne drive axles with differential and cross locks\* - design GCW 100tonnes. \* Cross locks replaced by a dog clutch if tandem axle lift is specified.
- **RTS2370A** RTS2370A single reduction tandem 23tonne drive axles with differential and cross locks\* - design GCW 70tonnes. \* Cross locks replaced by a dog clutch if tandem axle lift is specified.

### PACKAGES

- **LHFP-VE** Long Haul Fuel Economy driving package
- **LHFP-VE+** Long Haul Fuel Economy plus driving package

- Standard Equipment
- Optional Equipment

For more detailed information about cab and powertrain equipment, please refer to separate specification sheets.

For all possible options and combinations of options please consult your Volvo sales contact who can create a specification to match your requirements using the Volvo Sales Support system (VSS).

The factory reserves the right to modify design and change equipment without previous notification. The specification can vary from country to country.

- **DRIV16++** Cab Package: Drive ++
  - **DRIVE16+** Cab Package: Drive +
  - **1BED** Living package with single bed:
  - **1BED+** Living package with single bed plus:
  - **2BED** Living package with two beds:
  - **2BED+** Living package with two beds plus:
  - **AUDHIG** High Power Audio system: RDS radio with CD player - also playing MP3/WMA files from CD -, with integrated bluetooth phone and USB/Line inputs. FM/AM antenna, speakers in dashboard, doors, and sleeping compartment. AM/FM Bluetooth radio without CD player. USB and Aux line inputs. Speakers in dashboard, doors, and sleeping compartment. 7" touch screen with personal apps.
  - **MEDIA** AM/FM Bluetooth radio without CD player. USB and Aux line inputs. Speakers in dashboard, doors, and sleeping compartment. 7" touch screen with personal and professional apps. Dynafleet vehicle on-board data display with office internet support.
  - **MEDIA DF** AM/FM Bluetooth radio without CD player. USB and Aux line inputs. Speakers in dashboard, doors, and sleeping compartment. 7" touch screen with personal and professional apps. Dynafleet vehicle on-board data display with office internet support.
  - **MEDIA NAV** AM/FM Bluetooth radio without CD player. USB and Aux line inputs. Speakers in dashboard, doors, and sleeping compartment. 7" touch screen with personal and professional apps. Truck based satellite navigation (live updates not included) AM/FM Bluetooth radio without CD player. USB and Aux line inputs. Speakers in dashboard, doors, and sleeping compartment. 7" touch screen with personal and professional apps. Truck based satellite navigation (live updates not included) AM/FM Bluetooth radio without CD player. USB and Aux line inputs. Speakers in dashboard, doors, and sleeping compartment. 7" touch screen with personal and professional apps. Truck based satellite navigation (live updates not included) Dynafleet vehicle on-board data display with office internet support.
  - **VISI15** Visibility Package
  - **VISI15+** Visibility Plus Package
  - **VISIC15** Visibility Package
  - **ASAF15** Active Safety Package
  - **RCHAPAC1** Chassis Package Rigid
- ### CHASSIS
- **FST-AIR** Front suspension type - air
  - **FST-PAR** Front suspension type - 2 leaf parabolic springs
  - **FST-PAR3** Front suspension type - 3 leaf parabolic springs
  - **FSL5-BAS** Front suspension levelling - basic stroke
  - **FSL5-HI** Front suspension levelling - high stroke for demount operations - check with bodybuilder
  - **FAL10.0** Front axle design capacity 10 tonnes - Ensure that you have checked the tyre load index
  - **FAL8.0** Front axle design capacity 8.0 tonnes - Ensure that you have checked the tyre load index
  - **FAL8.5** Front axle design capacity 8.5 tonnes
  - **FAL9.0** Front axle design capacity 9.0 tonnes - Ensure that you have checked the tyre load index
  - **FSM-LUB** Lubricated rear shackles on front suspension pins and bushings
  - **FSTAB** Front anti-roll bar
  - **FSTAB2** Front anti-roll bar medium stiffness
  - **FSTAB3** Front stiff anti-roll bar
  - **RAL21** Rear bogie design capacity 21 tonnes
  - **RAL23** Rear bogie design capacity 23 tonnes
  - **RAL26** Rear bogie design capacity 26 tonnes
  - **RSTAB1** Rear anti-roll bar
  - **RSTAB3** Rear stiff anti-roll bar
  - **RALIM105** Rear axle load limiter, 10.5 tonnes
  - **RALIM115** Rear axle load limiter, 11.5 tonnes
  - **RALIM13** Rear axle load limiter, 13 tonnes
  - **RALIM95** Rear axle load limiter, 9.5 tonnes
  - **ACTST-TO** Volvo Dynamic Steering (VDS) with with extra electronic pump and torque overlay

# MODEL RANGE

## FH 16 6x4 Platform - Rear Air Suspension FH 64 R6HA

- ASFE-BAS** Active steering feature - Basic - Volvo Dynamic Steering only
- ASFE-PS** Active steering feature - Volvo Dynamic Steering with personal settings
- PSP-FIX** Power steering pump with fixed displacement
- PSP-VAR** Power steering pump with variable displacement
- EBS-MED** EBS medium package including "hill" hold function
- AUXPARK** Additional spring parking brakes
- FRAME266** Frame rail section external height 266 mm
- FRAME300** Frame rail section external height 300 mm
- FST7070** Frame thickness - web and flange 7.0mm
- FST8080** Frame thickness - web and flange 8.0mm
- FIL-EEEB** Inner liner from end of engine to end of bogie
- FIL-EEEF** Inner liner from end of engine to end of frame
- FIL-FBEB** Inner liner over rear bogie
- FIL-FBEF** Inner liner from front of bogie to end of frame
- FIL-TXEB** Inner liner from gearbox member to end of bogie
- FIL-TXEF** Inner liner from gearbox member to end of frame
- BBOX-L** Battery box located on left hand side
- BATS-D** Dual energy battery system - 2 living batteries and 2 starter batteries.
- BATS-S** Single energy battery system (2 batteries)
- 2BAT210B** 2 x 210 Ah capacity Gel batteries
- 2BATT225** 2 x 225 Ah capacity batteries
- BATTAMP** Battery voltage and ampere gauge
- BATTIND** Battery charge indication
- ADR2** ADR package for transportation of dangerous goods on road (Note does NOT include safe loading pass package if required this is quoted separately)
- MSWI-A** Main switch - ADR switch circuit shut down
- MSWI-C** Main switch - Chassis mounted toggle switch by battery box
- MSWI-R** Main switch - Key fob operated remote controlled
- R330A71** Right aluminium 710 mm D-shaped fuel tank, 330 litres volume  
Min volume 255l  
Max volume 885l
- UL-FUEL** Without left fuel tank  
Min volume 160l  
Max volume 730l
- ADTP-L** AdBlue tank on left hand side
- ADTP-R** AdBlue tank on right hand side
- ADB048** AdBlue tank usable volume 48 litres
- ADB064** AdBlue tank usable volume 64 litres
- ADB068** AdBlue tank usable volume 68 litres
- ADB090** AdBlue tank usable volume 90 litres
- ADB100** AdBlue tank usable volume 100 litres
- ADTC-BF** AdBlue tank cover with satin alloy look decorative cover
- FCAP-L** Locking fuel filler cap
- FUFF-AS** Fuel filling anti-spillage device
- FUFF-ATS** Fuel filling anti-theft and anti-spillage devices
- ESH-LEFT** Horizontal silencer, left exhaust outlet
- ESH-REAR** Horizontal silencer, rear exhaust outlet
- ESH-RIGH** Horizontal silencer, right exhaust outlet
- ESH-VERT** Horizontal silencer, vertical exhaust outlet
- EXST-SSP** Stainless steel exhaust stack - NOT polished
- EXST-ST** Steel exhaust stack
- HS-NAR** Narrow heat shield
- WHC-FIX2** Two fixed wheel chocks
- WHC-FOL2** Two foldable wheel chocks
- WHCP-F** Wheel chock(s) stored in the front part of the vehicle
- WHCP-M** Wheel chock(s) stored in the middle part of the vehicle
- WHCP-R** Wheel chock(s) stored in the rear part of the vehicle
- WHCP-T** Transport mounted wheel chock(s) stored in cab outer luggage locker
- TB-L80** Toolbox 800 mm, left side
- TB-R80** Toolbox 800 mm, right side
- SUP-BAS** EC approved chassis side guards
- SUP-LOW** EC approved low chassis side guards
- CHAIN-S** Snow chains
- HOOK-SC** Snow chain hooks
- TOWF-NO1** One front towing device
- TOWF-NO2** Two front towing devices
- TOWMBRH** Towing member, high mounted in centre of frame, D = 190
- TOWMBRL1** Towing member, low mounted under the frame
- TOWMBRL2** Towing member, low and forward mounted under the frame
- TOWMBRL3** Towing member, low and far forward mounted under the frame
- TOWMBRM** Towing member, medium mounted in line with frame lower flange
- RFEC-L** Rear frame end, lower flange cut for centre axle drawbar.
- RFEC-S** Rear frame end, straight cut for regular platform applications
- RFEC-U** Rear frame end, upper cut for tipper applications.
- C-RI4040** Towing coupling, Ringfeder 4040 G-150
- C-RI5055** Towing coupling, Ringfeder 5055 G-150
- C-RO400G** Towing coupling, Rockinger 400 G-150 for 40mm eyes
- C-RO50** Rockinger RO 50 50mm for centre axle trailer
- TOWR-ONE** Towing hitch attached to rear crossmember
- TREL-PK** Trailer electrical preparation kit - chassis/cab wiring
- TREL14** Single 14 pole electrical trailer connector
- TREL15** Single 15 pole electrical trailer connector - ADR certified
- TREL7** 7 pole - 24N trailer electrical suzie
- TREL7-7** 24N and 24S trailer electrical suzies
- TBC-DUO** Duomatic type air line connectors
- TBC-EC** Palm coupling type air line connectors
- TRBR-HCF** Full pressure hand controlled trailer brake
- TRBR-STA** Stationary trailer brake control
- TRB-STRE** Stretch Brake - Automatic low speed trailer brake activation to avoid jack-knifing and improve steerability
- RUP-FOLD** Folding EC approved aluminium rear underrun
- RUP-FOSL** Folding & sliding EC approved aluminium rear underrun
- RFEND-B** Three piece EC approved rear mud wings and spray flaps
- RFEND-T** Rear mud wings, transport mounted
- RFH-BAS** Basic rear wing height
- RFH-HIG** High rear wing height - higher wing tops
- RFH-LOW** Lower rear wing height - shallower wing tops
- AUXATNK** Auxiliary airtank
- ATANK-AL** Aluminium air tanks
- ATANK-ST** Steel air tanks
- RESTS-W** White conspicuity markings on chassis - sideguards, toolbox and rear overhang
- REST-RUP**
- TL-LED** Rear lights LED
- BLIGHT-E** Emergency brake light

### WHEELS & TYRES

- RT-AL** Alcoa brushed aluminium rims with standard holes for long stud fixing on all axles
- RT-ALDP** Alcoa Dura-Bright EVO aluminium rims with standard holes long stud fixing on all axles, requires cleaning with a ph neutral solution - washing up liquid.
- RT-ALDPD** Alcoa Dura-Bright EVO aluminium rims with countersunk holes for short stud fixing on all axles, requires cleaning with a ph neutral solution - washing up liquid.
- RT-ALDU** Alcoa brushed aluminium rims with countersunk holes for short stud fixing on all axles
- RT-STEEL** Steel rims on all axles

Standard Equipment

Optional Equipment

For more detailed information about cab and powertrain equipment, please refer to separate specification sheets.

For all possible options and combinations of options please consult your Volvo sales contact who can create a specification to match your requirements using the Volvo Sales Support system (VSS).

The factory reserves the right to modify design and change equipment without previous notification. The specification can vary from country to country.

# MODEL RANGE

## FH 16 6x4 Platform - Rear Air Suspension FH 64 R6HA

- WCAP** Aerodynamic hub caps
  - BRREC001** Bridgestone ECOPIA H - Energy rating C
  - BRREC002** Bridgestone Ecopia H 002 Evo - Tyre recommendation 2
  - COREC001** Continental ECOPLUS HS3 XL/HD3 - Energy rating B or C depending on size
  - COREC002** Continental ECOPLUS HS3/HD3 - Energy rating B or C depending on size
  - COREC003** Continental Efficient Pro S/D - Fuel Tyre Recommendation 3 Reduced mileage compared to Conti EcoPlus long haul pattern please consider when selecting these tyres.
  - GYREC001** Goodyear FUELMAX S/HL/D - Energy rating B or C depending on size
  - GYREC004** Goodyear FUELMAX S - Energy rating B depending on size
  - HAREC001** Hankook AL10+ E-Cube Max Long Haul Tyre - Energy rating B
  - HAREC002** Hankook AL10+ E-Cube Long Haul Tyre - Energy rating B with wide single
  - MIREC001** Michelin XFA2/X-LINE Energy - Fuel tyre Recommendation 1
  - MIREC002** Michelin XZA2/X-LINE Energy - Fuel tyre Recommendation 2
  - MIREC003** Michelin X-LINE Energy - Fuel tyre Recommendation 3
  - MIREC004** Michelin X Line Energy F/D2 - Energy rating A
  - PIREC001** Pirelli FH:01 Proway - Long Haul Tyre - Energy rating B
  - PIREC002** Pirelli FH:01 II Long Haul Tyre - Energy rating B with wide single
  - SPWT-D** Spare wheel & tyre with rear tyre pattern
  - SPWT-F** Spare wheel & tyre with front tyre pattern
  - SWCP-LF** Spare wheel carrier on left side of chassis ahead of rear axle
  - SWCP-R** Rear mounted spare wheel carrier
  - SWCP-T** Spare wheel supplied temporarily strapped to chassis
  - SWCP-TP** Temporary spare wheel carrier on top of chassis frame
  - JACK-12T** 12 tonne bottle jack
  - JACK-15T** 15 tonne bottle jack
  - JACK-20T** 20 tonne bottle jack
  - TOOL-BAS** Basic Toolkit
  - TOOLKIT** Complete tool kit
  - INFLAHOS** Tyre inflation hose
  - GAUGE-TP** Tyre pressure gauge
- ### DRIVELINE EQUIPMENT
- ASO-C** Crawler gear - Ratio direct top gearbox 19:1 Ratio Overdrive gearbox 17:1
  - ASO-ULC** Ultra low crawler and crawler gear - Ratios direct top gearbox 32:1 and 19:1 Ratios Overdrive box 32:1 and 17:1
  - TRAP-HD** Reinforced gearbox application
  - TP-CON** Construction Package
  - TP-DIST** Distribution Package
  - TP-HD** I-shift software - Heavy duty for high GCW Special conditions apply consult Sales Engineering
  - TP-LONG** Long Haul Package
  - AMSO-AUT** Enhanced I-shift software with manual shift available in auto mode and kickdown facility on accelerator pedal
  - AVO-ENH** Enhanced software for off road driveability and starting
  - APF-ENH** I-shift enhanced PTO functions
  - RET-TH** Gearbox mounted retarder
  - TC-MAOH2** Extra high performance transmission oil cooler - air to oil with front mounted radiator
  - TC-MWO** Basic transmission oil cooler - water to oil
  - 2COM1100** Two cylinder, air compressor, 1100 litres per minute
  - 2COMP900** Two cylinder, air compressor, 900 litres per minute
  - CLU-AIRC** Clutchable air compressor
  - AIRIN-FR** Front air intake fitted to the underside of cab engine tunnel
  - AIRIN-HI** Roof mounted air intake behind cab on left hand side
  - AIRIN-LO** Low level air intake behind cab on left hand side
  - ACL1ST-S** Two stage air filter
  - 24AL120B** 120 amp alternator
  - 24AL150B** 150 amp alternator
  - CCV-C** Closed crankcase engine ventilation
  - CCV-OX** Closed crankcase ventilation for cold markets
  - PRIM-EL** Electrical priming pump
  - AF-R** Hot fuel recirculation heated fuel filter
  - FUEFE2LW** Large engine mounted dual fuel filter with water separator
  - FUEFE2SW** Small engine mounted dual fuel filter with water separator
  - EST-AID** Air inlet manifold starting heater element
  - 220EBH15** 220V/1.5Kw electric engine block heater
  - PTER-100** Rear engine mounted power-take-off with DIN 100 / ISO 7646 flange
  - PTER-DIN** Rear engine mounted PTO with DIN5462 (female) splined shaft for a close coupled pump. Models with 3 steering axles will use this to drive the steering pump (AUXPSP)
  - PTER1400** Rear engine mounted power-take-off with SAE 1410 flange
  - HPE-F101** Parker F1-101, engine mounted, fixed displacement, single flow, engine mounted hydraulic pump
  - HPE-F41** Parker F1-41, engine mounted, fixed displacement, single flow, engine mounted hydraulic pump
  - HPE-F51** Parker F1-51, engine mounted, fixed displacement, single flow, engine mounted hydraulic pump
  - HPE-F61** Parker F1-61, engine mounted, fixed displacement, single flow, engine mounted hydraulic pump
  - HPE-F81** Parker F1-81, engine mounted, fixed displacement, single flow, engine mounted hydraulic pump
  - HPE-T53** Parker F2-53/53, engine mounted, Fixed displacement, Twin flow engine mounted hydraulic pump
  - HPE-T70** Parker F2-70/35, engine mounted, Fixed displacement, Twin flow engine mounted hydraulic pump
  - HPE-V45** Parker VP1-45, variable displacement, single flow, engine mounted hydraulic pump
  - HPE-V75** Parker VP1-75, variable displacement, single flow, engine mounted hydraulic pump
  - PTR-D** Gearbox PTO for plug-in pump, 0.71xeng speed
  - PTR-DH** Gearbox driven high speed PTO for one plug-in hydraulic pump
  - PTR-DM** Gearbox driven medium speed PTO for one plug-in hydraulic pump
  - PTR-F** Gearbox driven PTO with rear flange connection
  - PTR-FH** Gearbox driven high speed PTO with SAE drive flange
  - PTR-FL** Gearbox driven low speed PTO with SAE drive flange
  - PTRD-D** Gearbox driven HIGH SPEED PTO for two plug-in hydraulic pumps
  - PTRD-D1** PTRD-D1 Gearbox driven HIGH SPEED PTO (1 SAE flange & 1 plug-in hydraulic pump)
  - PTRD-D2** Gearbox driven HIGH SPEED PTO (2 SAE flanges & 1 plug-in hyd pump)
  - PTRD-F** PTO with 1 DIN + 1 flange connection rear, manual gearbox
  - HPG-F101** Parker F1-101 gearbox mounted, fixed displacement, single flow, hydraulic pump
  - HPG-F41** Parker F1-41 gearbox mounted, fixed displacement, single flow, hydraulic pump
  - HPG-F51** Parker F1-51 gearbox mounted, fixed displacement, single flow, hydraulic pump
  - HPG-F61** Parker F1-61 gearbox mounted, fixed displacement, single flow, hydraulic pump
  - HPG-F81** Parker F1-81 gearbox mounted, fixed displacement, single flow, hydraulic pump
  - EIDLESD** Engine idle shut down
  - DTRI-PER** Dashboard in darker peregrine greyish brown. Steering wheel grey and door panels in light beige for FH and black for FH16.
  - DTRI-SRA** Dashboard and steering wheel cover in light beige skylark. Door panels in light beige for FH and black for FH16.
  - STWPOS-R** RIGHT HAND DRIVE

Standard Equipment

Optional Equipment

For more detailed information about cab and powertrain equipment, please refer to separate specification sheets.

For all possible options and combinations of options please consult your Volvo sales contact who can create a specification to match your requirements using the Volvo Sales Support system (VSS).

The factory reserves the right to modify design and change equipment without previous notification. The specification can vary from country to country.

# MODEL RANGE

## FH 16 6x4 Platform - Rear Air Suspension FH 64 R6HA

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>■ <b>STWM-LE</b> Leather steering wheel</li> <li>□ <b>STGW-AD2</b> Adjustable steering wheel with neck tilt</li> <li>■ <b>STGW-ADJ</b> Adjustable steering wheel</li> <li>■ <b>AIRBAG</b> SRS Driver's air bag</li> <li>■ <b>DRC-AMII</b> DPF Regeneration control switch - for manual and switching off regeneration</li> <li>■ <b>1DAYDIG2</b> Continental VDO DTCO 4.0 smart tachograph<br/>This tachograph can ONLY offer remote download if the option of Dynafleet or an FMS gateway has been specified with this order.</li> <li>□ <b>1DAYDIGP</b> Continental VDO DTCO 3.0 digital tachograph<br/>For vehicles with long lead time - this includes prep kit for the retrofit of DTCO 4.0 tachograph.<br/>For updating to new legal demand for truck registration from 15th June 2019.<br/>This tachograph can ONLY offer remote download if the option of Dynafleet or an FMS gateway has been specified with this order.</li> <li>□ <b>ARSL</b> Additional road speed limit - switch in dashboard</li> <li>□ <b>CRUIS-E</b> Eco cruise control (with eco-roll and I-cruise, controls in steering wheel)</li> <li>■ <b>CRUISEC</b> Cruise control, standard</li> <li>■ <b>ESP-BAS1</b> Electronic Stability Control</li> <li>□ <b>ESPC-RO</b> ESP (Electronic Stability Program) functionality control - Reduced / Off</li> <li>□ <b>HWSS-ACB</b> Adaptive cruise control ACC with forward collision warning and AEBs advanced emergency brake system</li> <li>■ <b>HWSS-FCB</b> Forward collision warning with AEBs advanced emergency brake system</li> <li>■ <b>LSS-DW</b> Lane departure-warning system</li> <li>□ <b>LCS</b> Lane change support</li> <li>□ <b>DAS-W</b> Driver Alert Support system</li> <li>□ <b>RSENS-W</b> Rain sensing windscreen wipers</li> <li>■ <b>CU-ECC</b> Electrically controlled air conditioning with sun sensor</li> <li>□ <b>CU-ECC2</b> Electrically controlled air conditioning with sun sensor, mist sensor, air quality sensor and carbon filter</li> <li>■ <b>IMMOBIL</b> Thatcham H2 approved immobiliser</li> <li>□ <b>ALARM-B</b> Thatcham H1 approved vehicle alarm - Cab only</li> <li>□ <b>ALARM-E</b> Enhanced vehicle alarm - Thatcham H1 approved - Cab plus external sensor for body/trailer</li> <li>□ <b>ALCOLOCK</b> Alcolock</li> <li>□ <b>AMPL400</b> Radio amplifier, 8 channel, 400 W with subwoofer<br/>Located in right hand external storage box</li> <li>□ <b>BUPMON</b> Back up monitor with built in 7" screen on dash and one colour camera supplied loose for fitment by bodybuilder.<br/>Can accommodate up to 4 cameras for TfL Safe Scheme, CLOCS and FORS.</li> <li>□ <b>PHONE-PK</b> Telephone preparation kit (antenna, antenna attachm. cable incl.)</li> <li>■ <b>WLIFT-AD</b> Electrical window lift, automatic up/down driver side</li> <li>□ <b>ISUNS-BS</b> Side interior sun visor on both sides</li> <li>■ <b>ISUNS-DS</b> Driver's side interior sun visor</li> <li>□ <b>ISUNF-RE</b> Electrically operated textile interior sun blind</li> <li>■ <b>ISUNF-RM</b> Manually operated textile interior sun blind</li> <li>■ <b>CSPL-BX</b> Lower center dash open storage box</li> <li>□ <b>CSPL-BXD</b> Lower centre dash drawer</li> <li>□ <b>CSPU-SDR</b> One open storage and one drawer - behind push open lid - in upper part of the centre dash panel</li> <li>■ <b>CSPU-SS</b> Two open storages - behind push open lid in upper part of the</li> </ul> | <ul style="list-style-type: none"> <li>□ <b>ADFS</b> Two extra DIN slots in front shelf - can be fitted with card or drawer available as an accessory</li> <li>■ <b>BUPALARM</b> Reverse alarm</li> <li>□ <b>RTOLL-PK</b> Road toll PREPARATION kit for trucks operating with "Toll Collect" in Germany</li> <li>□ <b>LOADIND</b> Load indicator with central dashboard display</li> <li>□ <b>REMC-MF</b> Multi-functio wireless remote control</li> <li>□ <b>FIREXT3S</b> 3kg fire extinguisher mounted on seat base</li> <li>□ <b>WARNVEST</b> High visibility warning vest - no sleeves</li> <li>□ <b>AIDKIT</b> First aid kit</li> <li>□ <b>AIDKIT1B</b> First aid kit</li> <li>□ <b>WARNLAMP</b> Portable warning lamp</li> <li>□ <b>LAMP-IN</b> Inspection lamp</li> <li>□ <b>BULBKIT</b> Bulb and fuse kit</li> <li>■ <b>WRITEPAD</b> Writing pad</li> <li>□ <b>UPHTRI04</b> Interior trim:<br/>Seats: Black/green textile insert, black leather bolster &amp; green/yellow leather side insert<br/>Cab walls: Soft textile with matching grey, green and black colours</li> <li>□ <b>UPHTRI05</b> Interior trim:<br/>Seats: Light grey leather insert and black leather bolster Cab walls: In matching grey vinyl</li> <li>□ <b>UPHTRI08</b> Interior trim:<br/>Seats: Black with green perforated leather insert and yellow side edging<br/>Cab walls: soft textiles in matching grey, green and black</li> <li>■ <b>DST-CF4</b> Driver seat, comfort, suspended, belt in seat</li> <li>□ <b>DST-CF5</b> Driver seat, comfort, suspended, belt in seat, electrically heated</li> <li>□ <b>DST-CF6</b> Driver seat, comfort, suspended, belt in seat, electrically heated, ventilated</li> <li>□ <b>DST-LUX1</b> Deluxe suspended drivers seat features: electrical adjustment with memory function, seatbelt in seat with heated &amp; ventilated cushions</li> <li>□ <b>DST-LUX2</b> Deluxe suspended drivers seat features: electrical adjustment with memory function, seatbelt in seat and heated cushions</li> <li>□ <b>SBD-RED</b> Red seat belts</li> <li>□ <b>SBPRE-DS</b> Driver seat belt pretensioner</li> <li>□ <b>PST-BAS1</b> Passenger seat - Fixed non suspended fold up with seatbelt mounted in cab</li> <li>□ <b>PST-BSL1</b> Passenger seat - Sliding non suspended fold up with seatbelt mounted in cab</li> <li>□ <b>PST-CF4</b> Passenger seat - Comfort suspended with seatbelt mounted in seat</li> <li>□ <b>PST-CF5</b> Passenger seat - Comfort suspended &amp; heated with seatbelt mounted in seat</li> <li>□ <b>PST-RX1</b> Passenger seat - Fixed non suspended, features: 90 degree rotation and tilt function with seatbelt mounted in cab</li> <li>□ <b>PST-RX2</b> Passenger seat - Fixed non suspended, features: 90 degree rotation, tilt and heated functions with seatbelt mounted in cab</li> <li>□ <b>PST-STD2</b> Passenger seat - Fixed non suspended with seatbelt mounted in cab</li> <li>■ <b>PST-STD4</b> Passenger seat - Standard suspended with seatbelt mounted in cab</li> <li>□ <b>SBPRE-PS</b> Passenger seat belt pretensioner</li> <li>■ <b>ARMRE-BB</b> Two armrests on both driver and passenger seat.</li> <li>■ <b>ARU-LEA</b> Leather upholstered armrest</li> <li>■ <b>GRABHI-L</b> Leather covered instep cab grab handle</li> <li>□ <b>FMAT-RUB</b> Rubber floor mats</li> <li>■ <b>FMAT-TX2</b> Textile and rubber floor mats</li> </ul> |
|---|--|

■ Standard Equipment                      □ Optional Equipment

For more detailed information about cab and powertrain equipment, please refer to separate specification sheets.

For all possible options and combinations of options please consult your Volvo sales contact who can create a specification to match your requirements using the Volvo Sales Support system (VSS).

The factory reserves the right to modify design and change equipment without previous notification. The specification can vary from country to country.

# MODEL RANGE

## FH 16 6x4 Platform - Rear Air Suspension FH 64 R6HA

- **LBK80F** Lower fixed bunk with wide middle section 815 in the centre x 2000 mm
- **LBK80FRE** Lower electrically operated recline bunk with wide middle section 815 in the centre x 2000 mm
- **LBK80FRM** Lower manually operated recline bunk with wide middle section 815 in the centre x 2000 mm
- **MATL-FI** Firm lower bunk pocket sprung mattress
- **MATL-SF** Lower flexizone mattress - semi-firm, pocket springs up to 100kg - 16 stone
- **MATL-SO** Lower flexizone mattress - soft, pocket springs up to 85kg - 13.5 stone
- **OLMAT-BA** 35mm mattress overlay protector
- **OLMAT-PR** 50mm premium mattress overlay protector
- **TBK60AD** Height adjustable foldable top bunk 600 x 1900mm
- **TBK60F** Fixed foldable top bunk 600 x 1900mm
- **TBK70AD** Height adjustable foldable top bunk 700 x 1900mm
- **TBK70F** Fixed foldable top bunk 700 x 1900mm
- **PH-CAB2** 1.8kW Air to air night heater
- **PH-ENGCA** Engine and cab night heater
- **CPC-ADV** I-ParkCool - Advanced cab parking cooler with 120V DC electrical compressor
- **SLCP-BAS** Basic sleeper control panel - includes interior light, parking heater, roof hatch and door lock
- **SLCP-LUX** Luxury sleeper control panel - includes interior light, parking heater, roof hatch, door lock, alarm clock, window and radio
- **SAFE** Safe box for driver's personal items
- **RUS-BAS** Rear cab upper storage 154 litres - 300 mm high
- **RUS-HIG** Rear cab upper storage 245 litres - 440 mm high
- **TABLE** Folding and height adjustable table - on lower bunk
- **REFR-RUS** Fridge: 28 litre rear upper wall mounted with dividers
- **REFRIG** Fridge: 33 litre under bunk mounted with freezer dividers
- **MICRO-PK** Preparation kit for microwave oven (wiring)
- **BOTH-D** One bottle holder under dashboard centre section
- **BOTH-DL** Two bottle holders, one under dashboard centre section and one mounted to the under bunk drawer
- **BOTH-L** One bottle holder mounted to the under bunk drawer
- **COFMA-PK** Coffee maker, preparation kit.
- **INLI-BAS** Interior white LED lights - basic
- **INLI-NL** Interior white and red night LED light with no dimmer
- **INLI-NLD** Interior white and red night LED light with dimmer
- **ARL-FLEX** Two flexible reading lamps (snake lamps)
- **RH-EE** Without roof hatch - Tinted glass emergency exit ONLY
- **RH-ETR** Glass roof & escape hatch - Electrically operated, tinted glass with rear opening
- **RH-MTR** Glass roof & escape hatch - Manually operated, tinted glass with rear opening
- **URH** Without roof hatch
- **SWIND-BS** Extra side window on both sides behind "B" pillar
- **VANMIR** Vanity mirror in front shelf
- **AS-FUS** Extra shelf in front upper storage compartments
- **INFOT-PK** Preparation kit for the mounting of a flat screen TV in cab above the driver's door, includes bracket, electrical and speaker connections
- **DGLAS-L** Laminated door glass
- **LOCK-REM** Central locking with remote control
- **BUMP-B** Plastic front bumper
- **BUMP-B2** Steel front bumper
- **BUMP-HD** Heavy duty front bumper
- **BUMP-SP** Front bumper spoiler
- **GUARD-EH** Engine guard to protect sump and engine hoses
- **BUGNET** Insect screen in front of radiator
- **CTILT-P-E** Electrically operated hydraulic cab tilt
- **CTILT-P-M** Manually operated hydraulic cab tilt
- **FCABS-A** Front cab suspension - Air
- **FCABS-M** Front cab suspension - Mechanical spring
- **RCABS-A** Rear cab suspension - Air
- **RCABS-M** Rear cab suspension - Mechanical spring
- **HCC-INEX** Exterior and interior hood catch control
- **MIRCOMF** Electrically heated and operated main and wide angle mirrors and manually adjusted kerb view mirror on passenger side
- **MIRSTD** Electrically heated main and wide angle mirrors and manually adjusted kerb view mirror on passenger side
- **AMIR-F20** Auxiliary front view mirror with a 200mm radius
- **SUNV-H** External smoke grey sunvisor
- **AD-ROOF** Roof air deflector
- **AD-SIDES** Short cab side air deflector for rigid bodywork
- **HL-BASIC** Halogen H7 head lamps
- **HL-BHID** High intensity Bi-Xenon head lamps
- **HL-DBL** Bi-Xenon high intensity discharge and dynamic head lamps. Dipped beam follows the road, activated by a signal from the steering system.
- **HL-CLEAN** Head lamp cleaner - washer jets
- **HLP-ST** Headlamp protection
- **HL-ADJ** Headlight adjustment - Switch in cab
- **DRIVL2** Two spot lamps
- **UDRIVL** Without auxiliary driving lights
- **FOGL-WC** Front fog lights
- **CL-STAT** Static corner lights
- **ASL-RF2** Two Hella H11 70W spotlamps in sign box - only available with the basic headlight and no lower driving lights.
- **BEACO2F** Two front roof mounted amber beacon rotating warning lamps
- **BEACO2R** Two rear roof mounted (on accessory bracket) amber beacon flashing warning LED lamps
- **BEACON-P** Roof beacon wire preparation
- **BEACONA4** Four roof mounted (2 front/2 rear) amber beacon rotating warning lamps
- **CABPT-R1** Single outlet for roof mounted accessories
- **CABPT-R2** Twin outlets for roof mounted accessories.
- **SPOTP-F** Spotlamp preparation in front, max 280W
- **SPOTP-R** Spotlamp preparation on roof, max 280W
- **SPOTP-RF** Spotlamp preparation on cab roof and in cab front, max 2x280W
- **ROS-IL2** Preparation kit for illuminated roof sign with switch loose in cab, fit after registration
- **CSGN-ENG** Engine size and power headboard logo
- **CSGN-GTR** "Globetrotter" headboard logo
- **HORN-F1S** Single tone Jericho air horn chassis mounted
- **HORN-R2S** Two roof mounted air horns
- **ANT-CBR** Roof mounted antenna for CB radio, single aerial
- **ACCBR-AP** Front, middle & rear roof mounted accessory brackets
- **ACCBR-F** Front roof mounted accessory bracket

### Standard Equipment

### Optional Equipment

For more detailed information about cab and powertrain equipment, please refer to separate specification sheets.

For all possible options and combinations of options please consult your Volvo sales contact who can create a specification to match your requirements using the Volvo Sales Support system (VSS).

The factory reserves the right to modify design and change equipment without previous notification. The specification can vary from country to country.

# MODEL RANGE

## FH 16 6x4 Platform - Rear Air Suspension FH 64 R6HA

- **ACCBR-FM** Front & middle roof mounted accessory brackets
- **ACCBR-FR** Front & rear roof mounted accessory brackets
- **ACCBR-M** Middle roof mounted accessory bracket
- **ACCBR-R** Rear roof mounted accessory bracket
- **ACCBR-RM** Rear & middle roof mounted accessory brackets

- **STUC-B** Left and right storage compartments under cab
- **STUC-L** Left storage compartment under cab
- **STUC-R** Right storage compartment under cab

- **REFS-CW** White cab conspicuity markings mounted on cab side
- **REFS-TW** White cab conspicuity markings by packed in cab
- **REFS-TY** Yellow cab conspicuity markings by packed in cab

### SUPERSTRUCTURE PREPARATIONS

- **SW745-EE** Swapbody equipped with front stop block for wheelbase 4600 mm and body length 7150/7450 mm. Height 130 mm above frame.
- **SW745-GE** Swapbody equipped with front stop block for wheelbase 4600 mm and body length 7150/7450 mm. Height 190 mm above frame.
- **SW782-ME** Swapbody equipped with front stop block for wheelbase 4900 mm and body length 7150/7450/7820 mm. Height 130 mm above frame.
- **SW782-OE** Swapbody equipped with front stop block for wheelbase 4900 mm and body length 7150/7450/7820 mm. Height 190 mm above frame.
- **CROSSRE** Cross reinforcement for swapbody
- **SRWL-PK** Wiring preparation for side & rear work/reverse lamps on side of chassis and a three-position switch, maximum 280W
- **SWL-2FW** Two H3 70W white front chassis mounted (LH/RH side) working lamps and a 2-position switch (On/Off)
- **SWL-2RW** Two H3 70W white rear chassis mounted (LH/RH side) working lamps and a 2-position switch (On/Off)
- **SWL-4W** 4 H3 70W white front (2) & rear (2) chassis mtd (LH/RH side) working lamps & 2-pos switch (On/Off)
- **SWL-PK** Wiring preparation for side work/reverse lamps on side of chassis and a three-position switch, maximum 280W
- **WLC-H2W** Two H3/70W white working lamps high mounted on the back of cab
- **WLC-PKCH** Preparation kit (cables and switch) for cab mounted chassis working lamp
- **WLC-PKH** Preparation kit, cables and switch for high mounted working lamps back of cab
- **WLC-PKL** Preparation kit, cables and switch for low mounted working lamps back of cab
- **WLC-PKLH** Preparation kit - cables and switch for low and high mounted working lamps back of cab.
- **ECBB-BAS** Body builder electrical centre without body builder module
- **ECBB-HIG** Body builder electrical centre with body builder module
- **BBCHAS1** One 7-pole connector for Body builder interface
- **BBCHAS3** Three 7-pole connectors for Body builder interface
- **BEPR-T2** Body builder electrical software preparation for tipper with remote control
- **EXSTER** External steering control, with VDS and bodybuilder module
- **TD-LED** Trailer detection with LED sensing
- **FRFS-BS** Frame rail free space on both sides to give space for crane legs or other equipment.
- **FBA-BTF** Lower front body attachments for torsionally flexible - platform body
- **FBA-BTSF** Lower front body attachments for torsionally semi-flexible body - box or curtainsider
- **HBA-FSFB** Holes for body attachments - flexible/semi-flexible body
- **HBA-SB** Holes for body attachments - stiff body
- **RBA-T2** Lower rear body attachments for helper frame
- **CRANEPK1** Crane plates mounted to frame, for cranes up to 10 tonne metre capacity
- **CRANEPK2** Crane plates mounted to frame, for cranes up to 20 tonne

- **CRANEPK4** Crane plates mounted to frame, for cranes up to 40 tonne metre capacity
- **AUXL-SPK** Electrical preparation kit - wiring and switch for snow plough lights
- **TAILPRE2** Tail lift preparation kit, wireless remote operation
- **TAILPREP** Taillift preparation kit - cab switch and warning in driver display
- **AESW2** Two Body builder bistable electrical switches (marked AUX1 / AUX2)
- **AESW2PK** 2 Body builder bistable el.switches (marked AUX1/AUX2) and prep. for 4 more switches
- **AUXSW-4** Wiring for 4 extra switches (from Body builder electrical centre to switch positions)

### DELIVERY SERVICES

- **TGW-4GWL** GSM/GPRS/4G modem, LTE & WLAN for telematics gateway
- **FMS-PK** Fleet Management System gateway

**VOLVO**

Volvo Truck Corporation

volvotrucks.com